
Hypertherm[®]

HyPrecision™ Predictive Waterjet pumps

Improving productivity through prediction







New HyPrecision™ Predictive pumps

Designed and built to keep you up and running

Our newest generation HyPrecision pumps are the first waterjet pumps to incorporate predictive maintenance capabilities that substantially reduce maintenance costs and disruption caused by non-planned service. Equipped with standard features such as our proven Advanced Intensifier Technology and a closed loop proportional pressure control, our new pumps offer you even more consistent cut quality while ensuring trouble-free operation and reliability.

Increased productivity and reduced maintenance costs

Patented Seal Maintenance Technology™ extends seal life by up to 40%. The system monitors weepage and lets you know when it's time to change intensifier seals – no more costly changing too soon or too late! This increases productivity, minimizes scrap, and saves time, aggravation, and money.



Improved reliability and ease of service

With 10% fewer parts than earlier generations, new HyPrecision Predictive pumps include user-friendly features such as a color-coded junction box, electrical cable harnesses, quick-connect fittings, and an easy access bleed-down valve to make maintenance faster, easier, and less expensive.



Increased performance

Standard on all HyPrecision Predictive pumps, closed loop proportional pressure control adjusts for ambient pressure and temperature, oil viscosity and hydraulic system wear parts, to deliver consistent quality at optimum cutting speeds.



Improved safety

Standard for "S" series pumps, clear window cover lets the operator see the intensifier and attenuator. Optional interlocks help prevent unauthorized access, and can be programmed to automatically stop the pump when opened. In addition, the seal maintenance technology's drip tray helps keep the top deck – and the shop floor – clear of oil and water.



Seal Maintenance Technology™ boosts productivity and improves shop safety

Say goodbye to messy puddles in the workspace and unplanned downtime due to seal failure. Hypertherm's patented Seal Maintenance Technology eliminates the guess work with today's intensifier seal repair. Only from Hypertherm – an unstoppable force in waterjet!




Seal maintenance indicator

Continuously monitors intensifier weepage - blue lights blink when fluid passes by

Fluid capturing vessel

Captures intensifier weepage to help keep your floor clean



Choosing the right HyPrecision™ Predictive pumps for your application

System specifications







Pump model number		HyPrecision P-15			HyPrecision P-30			HyPrecision P-50			
Hz		50 60		50	0 60		50	60			
GENERAL	Maximum output: gpm (lpm)	0.30 (1.14)			0.60 (2.27)			1.0 (3.79)			
	Maximum orifice: inch (mm)	0.007 (0.18)			0.011 (0.28)			0.014 (0.35)			
	Output pressure	Adjustable to 60,000 psi (4100 bar)									
	Pressure control	Closed loop proportional pressure control – standard equipment									
	Bleed down valve	Air-actuated									
PUMP POWER	Motor power: HP (kW)	15 (11)			30 (22)			50 (37)			
	Voltage	400	208-230	460	400	208-230	460	400	208-230	460	
	Full load amps	24.9	45.8-41.6	20.8	46.9	84.9-77	38.5	73.8	138.2-125.8	61.9	
E E	Main breaker (amps)	25	50	25	50	200	50	80	150	80	
	Motor starter (options if more than 1 listed)	Across-line			Soft Start	Across-line	Soft Start or Across-line	Soft Start	Wye Delta	Soft Start or Wye Delta	
IAL IRES	Seal Maintenance Technology	Included as standard equipment									
SPECIAL FEATURES	Closed loop proportional pressure control	Included as standard equipment									
PHYSICAL	Width	36" (914 mm)									
	Length	73" (1849 mm)									
	Height	54" (1361 mm)									
	Operating weight lbs. (kg)		2200 (1000)		2400 (1100)			2600 (1200)			
	Cover	Optional steel cover									
ACCESSORIES	Boost pump	Optional									
	External air over oil cooling	Optional									
	Electrical Interlock	Optional									
	Chiller for oil cooling	Optional									
* Pump	s shown with optional steel cover										








Pump model number		HyPrecision P-50S		HyPrecis	ion P-60S	HyPrecision P-75S					
Hz	50	6	0	50	60	50	60				
Maximum output: gpm (lpm)	1.0 (3.79)			1.2 (4.54)	1.5 (5.68)					
Maximum orifice: inch (mm)		0.014 (0.35)		0.016	(0.40)	0.017 (0.43)					
Output pressure	Adjustable to 60,000 psi (4100 bar)										
Pressure control	Closed loop proportional pressure control – standard equipment										
Bleed down valve	Air-actuated										
Motor power: HP (kW)	50 (37)			60 (44.7)	75 (56)					
Voltage	400	208–230	460	400	460	400	460				
Full load amps	73.8	138.2-125.8	62.9	90.7	74.4	110.3	89.6				
Main breaker (amps)	80	150	80	100	100	125	100				
Motor starter (options if more than 1 listed)	Soft Start										
Seal Maintenance Technology	Included as standard equipment										
Closed loop proportional pressure control	Included as standard equipment										
Width	40" (1016 mm)										
Length	79" (1996 mm)										
Height	59" (1509 mm)										
Operating weight lbs. (kg)		2800 (1300)		3200	(1450)	3300 (1500)					
Cover	"S" series pumps include a cover with observation windows										
Boost pump	Included										
External air over oil cooling	Optional										
Electrical Interlock	Optional										
Chiller for oil cooling	Optional										
	Maximum output: gpm (lpm) Maximum orifice: inch (mm) Output pressure Pressure control Bleed down valve Motor power: HP (kW) Voltage Full load amps Main breaker (amps) Motor starter (options if more than 1 listed) Seal Maintenance Technology Closed loop proportional pressure control Width Length Height Operating weight lbs. (kg) Cover Boost pump External air over oil cooling Electrical Interlock	Maximum output: gpm (lpm) Maximum orifice: inch (mm) Output pressure Pressure control Bleed down valve Motor power: HP (kW) Voltage 400 Full load amps 73.8 Main breaker (amps) 80 Motor starter (options if more than 1 listed) Seal Maintenance Technology Closed loop proportional pressure control Width Length Height Operating weight lbs. (kg) Cover Boost pump External air over oil cooling Electrical Interlock	Maximum output: gpm (lpm) 1.0 (3.79) Maximum orifice: inch (mm) 0.014 (0.35) Output pressure Pressure control Bleed down valve Motor power: HP (kW) 50 (37) Voltage 400 208–230 Full load amps 73.8 138.2–125.8 Main breaker (amps) Motor starter (options if more than 1 listed) Seal Maintenance Technology Closed loop proportional pressure control Width Length Height Operating weight lbs. (kg) 2800 (1300) Cover Boost pump External air over oil cooling Electrical Interlock	Maximum output: gpm (lpm) 1.0 (3.79) Maximum orifice: inch (mm) 0.014 (0.35) Output pressure Pressure control Closed loop propor Bleed down valve Motor power: HP (kW) 50 (37) Voltage 400 208-230 460 Full load amps 73.8 138.2-125.8 62.9 Main breaker (amps) 80 150 80 Motor starter (options if more than 1 listed) Closed loop proportional pressure control Width Length Height Operating weight lbs. (kg) 2800 (1300) External air over oil cooling Electrical Interlock	Hz 50 60 50 Maximum output: gpm (lpm) 1.0 (3.79) 1.2 (4) Maximum orifice: inch (mm) 0.014 (0.35) 0.016 Output pressure Adjustable to 60,000 psi (410) Pressure control Closed loop proportional pressure control - : Closed loop proportional pressure control - : Bleed down valve Air-actuated Air-actuated Motor power: HP (kW) 50 (37) 60 (Voltage 400 208-230 460 400 Full load amps 73.8 138.2-125.8 62.9 90.7 Main breaker (amps) 80 150 80 100 Motor starter (options if more than 1 listed) Soft Start Soft Start Closed loop proportional pressure control Included as standard equipm Width 40" (1016 mm) 79" (1996 mm) Wighth 2800 (1300) 3200 Cover "S" series pumps include a cover with obsent pump Included External air over oil cooling Optional Electrical Interlock Optional	Maximum output: gpm (lpm)	Maximum output: gpm (lpm)				

The heart of every HyPrecision™ Predictive pump: Advanced Intensifier Technology providing the ultimate in waterjet reliability

By rethinking the way the intensifier pump works, we were able to make it work harder, last longer and require significantly less service time.



Easier servicing

Hydraulic rod seals and plunger bearings are readily accessible from outside the hydraulic end cap

Longer lasting

Advanced piston design minimizes seal wear and improves component life

Optimized shifting

Advanced electronics provide smooth, reliable shifting for optimum cut quality

No thread galling

Thread-less cylinders eliminate the possibility of galling (seizing up) and becoming unusable

Prolonged seal life

Large diameter ceramic plunger delivers more water per stroke with reduced friction, for longer seal life

Screw-less check valve

Eliminates possible loose screw creating internal damage to intensifier

Long life piston

Advanced piston design minimizes seal wear and improves component life


Large diameter plunger

1" (2.5 cm) plunger produces more water per stroke with reduced friction

A team to keep you up and running

Like you, we know that uptime is money. That's why we've put together an exceptional support team and all the information tools you need to stay ahead of unexpected problems and delays. It's all part of our commitment to service.

- Voicemail-free, expert waterjet support during business hours
- Global distribution ensures fast response and speedy parts delivery
- Hypertherm Waterjet Assistant mobile application for iOS and Android
- Online technical guides with step-by-step repair instructions
- Available on-site product training





Waterjet Assistant gives you instant access to detailed, step-by-step maintenance and repair procedures, including part numbers.

Get the mobile app

Download the Hypertherm Waterjet Assistant mobile app from the App Store for iOS or from Google Play for Android using the links below.











50 years of Shaping Possibility

With the right tools and a relentless focus on innovation, partnership, and community, we believe anything is possible.

Fifty years ago, in a small two car garage, Hypertherm® began our journey with simple, powerful ideas about business and an invention that shaped the future of industrial cutting. The same ideals that fueled our inception all those years ago are still what drive us today: A passion for challenging what is achievable with the products we create, the culture we foster, and the experience we deliver to our customers. As we look to the horizon and the next 50 years, we are proud that our people, partners, and innovations will shape the future with solutions that make anything possible for industries around the world.

At Hypertherm, we give shape to our customers' vision with the world's leading industrial cutting solutions. Every day we help individuals and companies around the world envision better, smarter and more efficient ways to produce the products that shape our world. So whether you're cutting precision parts in North America, constructing a pipeline in Norway, fabricating agricultural machinery in Brazil, cutting stone in Italy, gouging out welds in the mines of South Africa, or building a skyscraper in China, you can count on Hypertherm to help you not just cut parts but achieve your vision.

100% employee ownership matters

At Hypertherm, we are not just employees: we are all owners. Ownership is a powerful motivator that ensures our customers are our top priority. As owners, we make sure every product is built to the highest quality and that our service is second to none. And we build long-term relationships that deliver value for us, our partners and our customers.

Worldwide presence and strength

Hypertherm is a key partner for your fabrication needs and has built a global organization focused on providing high-performance cutting solutions.

Key elements of the Hypertherm formula include:

- Dedicated Associates focused on customer-centered product design and support
- · Local sales and service
- Broad application experience and proven results
- Sustainable and ethical business practices benefit our customers and communities



(800) 991-4225 www.ahbinc.com ISO Certified customerservice@ahbinc.com

Hypertherm wall of patents

HELPING YOU SHAPE THE WORLD.



PLASMA | LASER | WATERJET | AUTOMATION | SOFTWARE | CONSUMABLES

To learn more, visit www.hypertherm.com/waterjet



Hypertherm and HyPrecision are trademarks of Hypertherm, Inc. and may be registered in the United States and/or other countries.

Environmental stewardship is one of Hypertherm's core values, and it is critical to our success and our customers' success. We are striving to reduce the environmental impact of everything we do. For more information: www.hypertherm.com/environment.

© 9/2018 Hypertherm, Inc. Revision 0

897640





Greener

Cuts